




**Flexible, easy to install rubber speed bumps for speeds under 30 m.p.h.**

100% recycled rubber speed bumps for areas where vehicle speed is problematic. Rubber speed bump's superior construction resists warping, rotting, chipping and temperature differences. Designed for smooth rollovers.


Diagonal reflective yellow strips with "Cats Eye's" provide approaching motorists with an awareness of the necessity for speed reduction. Two models available: 4 foot and 6 foot with either glass eyes or top mounted markers for enhanced night visibility.

**RUBBER BUMPS**


**EASY ROLLOVER SPEED BUMPS**



**Easy Rider** type bumps are equipped with reflective yellow stripes and "Cat's Eye" glass beads.




**Glow Rider** type bumps are equipped with top mounted yellow 2 face prismatic reflective markers.




**Tiger Tooth** bumps are equipped with 8 "cat's eye" reflectors and yellow strips for enhanced night visibility.


Standard lengths and uniform sizes allow the bumps to be joined at the ends for greater lengths. Both models are available in 4 ft. and 6 ft. lengths.



**End caps** for speed bumps adapt to both Easy Rider and Glow Rider for smooth round roll overs.



**Channeled** underside has two 1 1/4" x 1" grooved conduits allowing for cable/piping protection and drainage.



**Dimensions** both models are sized at 2.25 inches in height x 12 inches in width.

**BENEFITS**

- 100% recycled rubber
- Reflective yellow paint
- Integrated reflectors
- Channeled underside
- 4 foot and 6 foot lengths
- Warping and rot resistant
- U.V. and oil resistant
- Lineal attachment capability
- Flexible and non conductive
- Temporary or permanent
- Optional end caps

**HIGHLY VISIBLE**



Glow Rider model with top mounted double faced prismatic markers.

**INSTALLATION**

**Asphalt**

**STEP ONE:** Drill a 1/2 inch hole with a masonry carbide bit.

**STEP TWO:** Insert 14" capped rebar spike into predrilled hole and hammer into position.

**Concrete**

Utilize 1/2" diameter lag bolts 5" in length.

**Anchors**

4 foot requires 3 spikes / lag bolts  
6 foot requires 4 spikes / lag bolts



Item #	Length	Description	Cost
355-4ER-SYP	4 ft.	Easy Rider	\$ 95.50
355-4GR-PM	4 ft.	Glow Rider	\$ 95.00
SB-4BK-3S8GB	4 ft.	Tiger Tooth	\$ 90.00
355-6ER-SYP	6 ft.	Easy Rider	\$125.00
355-6GR-PM	6 ft.	Glow Rider	\$125.00
SB-6BK-3S8GB	6 ft.	Tiger Tooth	\$115.00
355-END		Extrem element	\$ 15.00
315-5-LB	5 in.	Lag Bolt x 1/2"	\$ 1.80
357-14-SPK	14 in.	Spike	\$ 2.50